



CFA128015HS

80 x 80 x 15mm



CFA249225MS

92 x 92 x 25mm



CFA248025MS

80 x 80 x 25mm



CFA2412025MS

120 x 120 x 25mm



CFA2412038MS

120 x 120 x 38mm

80 x 80 x 15mm

MODEL NUMBER	VOLTAGE	POWER	BEARING	IMPELLER	SPEED	AIR FLOW	MAX PRESSURE	NOISE	WEIGHT	CONNECTION	APPROVAL
CFA128015HS <b>New!</b>	12 VDC	2.6 W	Sleeve	Plastic	3000 rpm	39 CFM	3.2mmH <sub>2</sub> O	35 dBA	59g	Wire leads	

80 x 80 x 25mm

MODEL NUMBER	VOLTAGE	POWER	BEARING	IMPELLER	SPEED	AIR FLOW	MAX PRESSURE	NOISE	WEIGHT	CONNECTION	APPROVAL
CFA128025LS	12 VDC	1.8 W	Sleeve	Plastic	2100 rpm	30 CFM	2.2mmH <sub>2</sub> O	23.7 dBA	85g	Wire leads	
CFA128025MB <b>New!</b>	12 VDC	2.4 W	Ball	Plastic	2700 rpm	37 CFM	3.2mmH <sub>2</sub> O	29.8 dBA	85g	Wire leads	
CFA128025MS	12 VDC	2.4 W	Sleeve	Plastic	2700 rpm	37 CFM	3.2mmH <sub>2</sub> O	29.8 dBA	85g	Wire leads	
CFA248025MS <b>New!</b>	24 VDC	4.8 W	Sleeve	Plastic	2700 rpm	37 CFM	3.2mmH <sub>2</sub> O	29.8 dBA	85g	Wire leads	

92 x 92 x 25mm

MODEL NUMBER	VOLTAGE	POWER	BEARING	IMPELLER	SPEED	AIR FLOW	MAX PRESSURE	NOISE	WEIGHT	CONNECTION	APPROVAL
CFA129225LS <b>New!</b>	12 VDC	1.9 W	Sleeve	Plastic	2000 rpm	41.5 CFM	2.3mmH <sub>2</sub> O	28 dBA	120g	Wire leads	
CFA129225MB <b>New!</b>	12 VDC	2.4 W	Ball	Plastic	2500 rpm	50.5 CFM	3.5mmH <sub>2</sub> O	34 dBA	120g	Wire leads	
CFA129225MS	12 VDC	2.4 W	Sleeve	Plastic	2500 rpm	50.5 CFM	3.5mmH <sub>2</sub> O	34 dBA	120g	Wire leads	
CFA249225MS <b>New!</b>	24 VDC	3.4 W	Sleeve	Plastic	2500 rpm	50.5 CFM	3.5mmH <sub>2</sub> O	34 dBA	120g	Wire leads	

120 x 120 x 25mm

MODEL NUMBER	VOLTAGE	POWER	BEARING	IMPELLER	SPEED	AIR FLOW	MAX PRESSURE	NOISE	WEIGHT	CONNECTION	APPROVAL
CFA1212025LS	12 VDC	1.7 W	Sleeve	Plastic	2000 rpm	61.4 CFM	2.9mmH <sub>2</sub> O	38 dBA	150g	Wire leads	
CFA1212025MB <b>New!</b>	12 VDC	3.0 W	Ball	Plastic	2500 rpm	74.5 CFM	3.8mmH <sub>2</sub> O	43.8 dBA	150g	Wire leads	
CFA1212025MS	12 VDC	3.0 W	Sleeve	Plastic	2500 rpm	74.5 CFM	3.8mmH <sub>2</sub> O	43.8 dBA	150g	Wire leads	
CFA2412025MS <b>New!</b>	24 VDC	4.3 W	Sleeve	Plastic	2500 rpm	74.5 CFM	3.8mmH <sub>2</sub> O	43.8 dBA	150g	Wire leads	

120 x 120 x 38mm (Die Cast Aluminum Frame)

MODEL NUMBER	VOLTAGE	POWER	BEARING	IMPELLER	SPEED	AIR FLOW	MAX PRESSURE	NOISE	WEIGHT	CONNECTION	APPROVAL
CFA1212038MB <b>New!</b>	12 VDC	12 W	Ball	Plastic	2400 rpm	121 CFM	5.6mmH <sub>2</sub> O	46 dBA	420g	Wire leads	
CFA1212038MS	12 VDC	12 W	Sleeve	Plastic	2400 rpm	121 CFM	5.6mmH <sub>2</sub> O	46 dBA	420g	Wire leads	
CFA2412038MS <b>New!</b>	24 VDC	14.4 W	Sleeve	Plastic	2400 rpm	121 CFM	5.6mmH <sub>2</sub> O	46 dBA	420g	Wire leads	