

LINEAR TRIPLE OUTPUT - DIGITAL (PREMIUM)

- Switchable Independent Series / Parallel Operation
- Two Variable 0-30VDC @ 3.0A Outputs
- Fixed 5 VDC @ 3.0A Output
- Constant Voltage / Constant Current
- LCD Voltage & Current Displays
- Two Year Warranty

Triple output constant voltage / constant current DC adjustable power supply. There are three modes of operation: Independent, Serial, and Parallel. In the Independent mode, there are two variable outputs: 0-30 VDC @ 3 Amps each and a constant 5 VDC @ 3 Amps. In Serial mode, the output is 0-60 VDC @ 3 Amps and a constant 5 VDC @ 3 Amps. In Parallel mode, the output is 0-30 VDC @ 6 Amps and a constant 5 VDC @ 3 Amps.

SPECIFICATIONS	PSB-330T
OUTPUT VOLTAGE	0-30, 0-30, 5VDC
OUTPUT CURRENT	3, 3, 3ADC
LOAD REGULATION	+/-0.01% +5mV
LINE REGULATION	+/-0.01% +3mV
RIPPLE AND NOISE	<0.3mV RMS
POWER REQUIREMENTS	120 VAC/60Hz
DIMENSIONS (WxHxD)mm	230 x 170 x 310mm (9.1 x 6.7 x 12.2")
WEIGHT	6.9Kg (15.2lbs)



2 x 0-30VDC @ 3A / 5VDC @ 3A
PSB-330T



LINEAR TRIPLE OUTPUT - DIGITAL (LIGHT DUTY)

SPECIFICATIONS	PSA-2530D
OUTPUT VOLTAGE	0-30, 12, 5VDC
OUTPUT CURRENT	2.5, 0.5, 0.5ADC
LOAD REGULATION	0.05% + 10mV
LINE REGULATION	0.05% + 10mV
RIPPLE AND NOISE	5mV RMS
POWER REQUIREMENTS	120VAC, 60Hz
DIMENSIONS (WxHxD)	150 x 145 x 200mm (6 x 5.75 x 7.875")
WEIGHT	2.8Kg (6.2lbs)

- Variable 0 - 30VDC @ 2.5A
- Fixed 12VDC @ 500mA
- Fixed 5VDC @ 500mA
- Dual LCD Meters
- Two Year Warranty



0-30VDC @ 2.5A / 12VDC @ 500mA / 5VDC @ 500mA
PSA-2530D

LINEAR TRIPLE OUTPUT - ANALOG

- Switchable Independent Series / Parallel Operation
- Two Variable 0-30VDC @ 3A or 5A
- Fixed 5VDC @ 3A
- Constant Voltage / Constant Current
- Coarse & Fine Adjustments
- Voltage & Current Meters
- Two Year Warranty

SPECIFICATIONS	PS-3330	PS-5330
OUTPUT VOLTAGE	0-30, 0-30, 5VDC	0-30, 0-30, 5VDC
OUTPUT CURRENT	3, 3, 3ADC	5, 5, 3ADC
LOAD REGULATION	±0.25% +3mV (1% to 100% of Rated Load)	
LINE REGULATION	±0.025% +2mV (10% Input Variation)	
RIPPLE AND NOISE	0.5mV RMS (to 10KHz)	
OUTPUT IMPEDANCE	0.2 Ohms (to 10KHz)	
POWER REQUIREMENTS	120VAC, 60Hz	
DIMENSIONS (WxHxD)	360 x 155 x 267mm (14.125 x 6 x 10.5")	360 x 155 x 267mm (14.125 x 6 x 10.5")
WEIGHT	9Kg (19.8lbs)	13.2Kg (29.2lbs)



2 x 0-30VDC @ 3A / 5VDC @ 3A
PS-3330
2 x 0-30VDC @ 5A / 5VDC @ 3A
PS-5330