

DC FANS



CFA124010MB

40 x 40 x 10mm



CFA124020MB

40 x 40 x 20mm



CFA126015MS

60 x 60 x 15mm



CFA126025MB

60 x 60 x 25mm



CFA125010MS

50 x 50 x 10mm

DC BRUSHLESS FANS

Circuit-Test DC fans offer high performance, efficiency and reliability. These industrial quality cooling fans are ideal for Data communications, Instrumentation & many other electronic applications. "Locked Rotor" Alarm sensor now standard on all DC models including the new series of 24VDC models are now available. Visit www.circuitest.com for more details.

CONSTRUCTION:

- Frame/Housing: Die-Cast Aluminum or Glass fibre reinforced plastic
- Impeller: Glass fibre reinforced plastic
- Bearing: Ball, Sleeve or Combination Ball/Sleeve
- Input Voltage: 5, 12 or 24 VDC
- Connection: 3 Wire leads (3rd wire "Locked Rotor" Alarm sensor)
- Approvals: CSA/IUL

AVAILABLE ACCESSORIES:

Finger Guards & Filters

40 x 40 x 10mm

MODEL NUMBER	VOLTAGE	POWER	BEARING	IMPELLER	SPEED	AIR FLOW	MAX PRESSURE	NOISE	WEIGHT	CONNECTION	APPROVAL
CFA054010HSB New!	5 VDC	1.2 W	Sleeve/Ball	Plastic	6500 rpm	7.7 CFM	2.4mmH ₂ O	29 dBA	18g	Wire leads	
CFA124010MB New!	12 VDC	1.1 W	Ball	Plastic	5000 rpm	6.5 CFM	1.9mmH ₂ O	24.5 dBA	18g	Wire leads	
CFA124010MS	12 VDC	1.1 W	Sleeve	Plastic	5000 rpm	6.5 CFM	1.9mmH ₂ O	24.5 dBA	18g	Wire leads	

40 x 40 x 20mm

MODEL NUMBER	VOLTAGE	POWER	BEARING	IMPELLER	SPEED	AIR FLOW	MAX PRESSURE	NOISE	WEIGHT	CONNECTION	APPROVAL
CFA124020MB New!	12 VDC	1.2 W	Ball	Plastic	6000 rpm	7.1 CFM	3.9mmH ₂ O	26.4 dBA	40g	Wire leads	
CFA124020MS	12 VDC	1.2 W	Sleeve	Plastic	6000 rpm	7.1 CFM	3.9mmH ₂ O	26.4 dBA	40g	Wire leads	
CFA124020HS	12 VDC	1.9 W	Sleeve	Plastic	7000 rpm	8.5 CFM	5.3mmH ₂ O	31 dBA	40g	Wire leads	
CFA244020MS New!	24 VDC	3.1 W	Sleeve	Plastic	6000 rpm	7.1 CFM	3.9mmH ₂ O	26.4 dBA	40g	Wire leads	

50 x 50 x 10mm

MODEL NUMBER	VOLTAGE	POWER	BEARING	IMPELLER	SPEED	AIR FLOW	MAX PRESSURE	NOISE	WEIGHT	CONNECTION	APPROVAL
CFA125010MS	12 VDC	1.2 W	Sleeve	Plastic	4000 rpm	8.8 CFM	1.5mmH ₂ O	29 dBA	20g	Wire leads	

60 x 60 x 15mm

MODEL NUMBER	VOLTAGE	POWER	BEARING	IMPELLER	SPEED	AIR FLOW	MAX PRESSURE	NOISE	WEIGHT	CONNECTION	APPROVAL
CFA126015MS New!	12 VDC	1.9 W	Sleeve	Plastic	3800 rpm	20.2 CFM	3.1mmH ₂ O	30.3 dBA	35g	Wire leads	

60 x 60 x 25mm

MODEL NUMBER	VOLTAGE	POWER	BEARING	IMPELLER	SPEED	AIR FLOW	MAX PRESSURE	NOISE	WEIGHT	CONNECTION	APPROVAL
CFA126025MB New!	12 VDC	1.3 W	Ball	Plastic	3200 rpm	16.7 CFM	3.1mmH ₂ O	25 dBA	75g	Wire leads	
CFA126025MS	12 VDC	1.3 W	Sleeve	Plastic	3200 rpm	16.7 CFM	3.1mmH ₂ O	25 dBA	75g	Wire leads	
CFA246025MS New!	24 VDC	2.4 W	Sleeve	Plastic	3200 rpm	16.7 CFM	3.1mmH ₂ O	25 dBA	75g	Wire leads	