

## MULTIMETERS - CLAMP-ON

### Clamp Meter - AC/DC, True RMS, CAT III, Backlight

- 3-1/2 digit LCD with Backlight
- AC Voltage to 600V, true RMS
- DC Voltage to 600V
- AC Current to 1000A
- DC Current to 1200A
- Resistance to 200KΩ
- Frequency to 20KHz (autoranging)
- Maximum display 1999
- Test leads and Battery included



MODEL	DESCRIPTION
DCL-320	Clamp Meter - AC/DC, True RMS, CAT III, Backlight

### Clamp Meter - AC/DC, CAT III

- AC/DC Voltage to 600V
- AC Current to 1000A
- DC Current to 1200A
- Resistance to 200KΩ
- Frequency to 20KHz (autoranging)
- Continuity buzzer, diode test
- 3-1/2 digit LCD
- Maximum display 1999
- Test leads and Battery included



MODEL	DESCRIPTION
DCL-310	Clamp Meter - AC/DC, CAT III

## SPECIALTY METERS

### Sound Level Meter with Data Logging

- Data logging
- Autoranging
- Range: 30 to 130dB, 31.5Hz to 8KHz
- Dynamic range: 50dB
- Accuracy: +/- 1.5dB
- Resolution: 0.1dB
- A & C Frequency weighting
- Data hold, Min/Max
- 3-1/2 digit LCD
- Auto power off
- Carrying case, windscreen, software, USB cable and 9V battery included



MODEL	DESCRIPTION
DMS-4420	Sound Level Meter with Data Logging

### Magnetic Field Meter (ELF/EMF)

- Range: 200/2000mG or 20/200uT
- Resolution: 0.1/1mG or 0.01/0.1uT
- Selectable between mini-Gauss and micro-Tesla
- Frequency response: 30 to 300Hz
- Sampling rate: 2.5 times per second
- Accuracy: +/- 2.5%
- Max Hold, Data Hold
- Single axis sensor
- 3-1/2 digit LCD
- Soft carrying case and 9V battery included



MODEL	DESCRIPTION
DME-3300	Magnetic Field Meter (ELF/EMF)

### Sound Level Meter, Autoranging

- Autoranging
- Range: 30 to 130dB, 30Hz to 8KHz
- Dynamic range: 50dB
- Accuracy: +/- 1.5dB
- Resolution: 0.1dB
- A & C Frequency weighting
- Data hold, Min/Max
- 3-1/2 digit LCD
- Auto power off
- Carrying case, windscreen and 9V battery included



MODEL	DESCRIPTION
DMS-4400	Sound Level Meter, Autoranging

### Light Meter

- Range: 20 to 20K fctd, 20 to 200K lux
- Silicon photo diode sensor and filter
- Sampling rate: 2.5 times per second
- Accuracy: +/- 3%
- Data hold, Min / Max functions
- Cosine angular corrected
- 3-1/2 digit LCD
- 9V battery, carrying case included



MODEL	DESCRIPTION
DML-2200	Light Meter