

# CIRCUIT-TEST

## RPT Series Power Adapters

- AC/DC Adapter - 12VDC 5A
- Energy Efficiency Level VI
- Universal Input (100 - 240 VAC)
- No Load Power Consumption <0.21W
- Over Voltage, Over Current and Short Circuit Protection
- UL, cUL Safety Approvals



### SPECIFICATIONS

<b>MODEL</b>	<b>RPT60-12-P5-A3</b>
<b>INPUT</b>	
Voltage	100 - 240 VAC
Frequency	50 - 60Hz
Current	1.4A Max
Inrush Current	80A Max (at 230VAC, full load, cold start, 25°C)
Power Consumption (no load)	< 0.21W (at 115VAC/230VAC)
<b>OUTPUT</b>	
Voltage	12VDC
Current	5A
Regulation	±5% Typical
Power	60W Max
Ripple & Noise	120mVp-p Max
<b>PROTECTIONS</b>	
Over Voltage Protection	Vout 150% Max
Short Circuit Protection	Output shutdown, auto recovery
Over Current Protection	Iout 180% Max
<b>SAFETY</b>	
Safety Approvals	UL, cUL,
Efficiency	DoE LEVEL VI, NRCan
Dielectric Strength	Primary to Secondary at 10mA for 1 minute: 3000Vac
Insulation Resistance	Primary to Secondary 500Vdc: 10Mohm
EMI/EMC	FCC Class B
Leakage Current	Less than 3.5mA
MTBF	300,000 hours (calculated at 25°C per Telcordia SR-332)
RoHS	Compliant
<b>ENVIRONMENTAL</b>	
Operating Temperature	0 to 40°C
Storage Temperature	-20 to +80°C
Operating Humidity	20 to 80% RH
Storage Humidity	10 to 90% RH

# CIRCUIT-TEST

## RPT Series Power Adapters

### MECHANICAL SPECIFICATIONS

MODEL	RPT60-12-P5-A3
Dimensions	115 x 53 x 38mm (LxWxH)
Weight	310g
Input Socket	IEC 60320 C14
Output Plug	2.1 x 5.5mm Plug, Centre Positive

